

Nuvair ERGO Stainless Compressors

SKU: 8023 / 8026

Price: ?0.00



Description

Features

- Ergonomic stainless steel frame
- Tri-chem breathing air purification system
- Disposable purification cartridge
- Manual condensate drains
- Pressure relief valve on all stages
- Emergency stop
- Motor starter
- Hour meter

Options

- Powder-coated steel frame (see [SKU 8023-IT / 8026-IT](#))
- Automatic condensate drains
- Pressure switch
- High temperature shutdown
- Low oil shutdown
- Interstage pressure gauges
- Visual carbon monoxide / moisture indicator

Specifications

Model	MCH13	MCH16
Fill Time*	~11 minutes	~9 minutes
Charging Rate*	8.4 SCFM (238 L/min)	11.3 SCFM (320 L/min)
CFM FAD	7 CFM (200 L/min)	9.4 SCFM (266 L/min)
230 V / E1 / 60 Hz	23 A 5.5 hp (4 kW) SKU 8023.1-SS	N/A
230 V / E3 / 60 Hz	14 A 5 hp (3.7 kW) SKU 8023.2-SS	20 A 7.5 hp (5.5 kW) SKU 8026.2-SS
380-415 V / E3 / 50 Hz	N/A	10 A 7.5 hp (5.5 kW) SKU 8026.6-SS
Yanmar Diesel	N/A	10 hp (7.5 kW) SKU 8026-DY-SS
Honda Gas Engine	N/A	11.7 hp (8.7 kW) SKU 8026-G-SS
Max Operating Pressure	5000 psi (345 bar)	5000 psi (345 bar)
Sound Level @ 3 m	81 dB	82 dB
Number of Fill Hoses	2	2
Condensate Drain	Manual	Manual
Dimensions (L x W x H)		37 x 23 x 25 in (94 x 58 x 64 cm)
Weight		306 lb (139 kg)
Lubrication		Splash
Air Quality	DIN 3188 - CGA Grade E - NFPA 1500 - EN12021	

*Based on 80 cu ft cylinder from 500 to 3000 psi.