

Mini Tech Kubota Diesel Air Compressor

SKU: 8038-DK-EL

Price: ?0.00



Description

The Kubota diesel-powered Coltri/Nuvair Mini Tech high pressure air compressor uses a pumping unit made from top quality materials; connecting rods from aluminum alloy, stainless steel intercoolers and aftercoolers that are more than four meters in length, and cylinders of special cast iron. The marine grade 6061 aluminum frame is corrosion resistant, rigid and lightweight.

Features

- 5000 psi (345 bar) maximum pressure
- Grade E breathing air filtration
- Two (2) fill whips
- Stainless steel intercoolers
- Four (4) lifting handles
- 6061 marine grade aluminum frame

Options

- Electric start
- Automatic condensate drains
- Pressure switch
- Hour meter
- High temperature shutdown
- Low oil shutdown
- Interstage pressure gauges
- Stainless steel frame
- Visual carbon monoxide/moisture indicator

- Wheels
- Tropical Plus compressor block with oil pump
- Filtration upgrade
- Lifting eyes
- Yanmar Diesel

Specifications

Model	Mini Tech MCH16
Fill Time*	Approximately 9 Minutes
Charging Rate*	11.3 SCFM (320 L/min)
CFM FAD	9.4 CFM (266 L/min)
Kubota Diesel	9.4 hp (7 kW)
RPM	3600
Sound Level @ 3 m	96 dB
Max Operating Pressure	5000 psi (345 bar)
Number of Stages	3
Number of Fill Hoses	2
Condensate Drain	Manual
Dimensions (L x W x H)	45.5 x 22.5 x 62.5 in (116 x 57 x 159 cm)
Weight	360 lb (163 kg)
Lubrication	Splash lubrication, capacity 1.8 L
Air Quality	DIN 3188 - CGA Grade E - NFPA 1500 - EN12021

*Based on 80 cu ft cylinder from 500 to 3000 psi.