

Traveler LP Portable Nitrox Membrane System

SKU: 7051-LP

Price: ?0.00



Description

Features

- Nuvair membrane rated for EANx40 @ 3.5 CFM (99 L/min)
- 110-220V 1200-watt membrane heater with thermostatic control
- LP-LP regulator gauges
- Static mixing tube and air intake filter
- Inline oxygen analyzer
- Nitrox intake hose and connections
- Bamax BX59 low-pressure compressor
- 15-gallon air storage tank
- Air aftercooler
- Hankison or Norgren low pressure filtration
- Pro O₂ Analyzer
- HP-LP regulator and reducer for Pro O₂ analyzer
- Motor control / starter
- Head unloader
- Hour meter

Includes

- 1-gallon compressor lubricant
- Owners Manual
- 25 nitrox tank wraps

Specifications

115V / E1 / 60 Hz	66A SKU 7051.0-LP
208-230V / E1 / 60Hz	33A SKU 7051.1-LP
208-230V / E3 / 60Hz	23A SKU 7051.2-LP
208-230V / E1 / 50Hz	SKU 7051.4-LP
Membrane Operating Pressure	80-165 psi (5.5-11 bar)
Membrane Supply Air Volume	4-16 CFM (113-453 L/min)
Membrane Optimum Temperature	110° ±5°F (43° ±3°C)
Power - Electric	5 hp (3.7 kW)
Power - Gas	5.5 hp (4 kW)
Dimensions (L x W x H)	49" x 24" x 9" (124 x 61 x 124 cm)
Weight	400 lb (181 kg)
Shipping Weight	490 lb (222 kg)

A high pressure compressor, such as the MCH6, is required.