

SPX Hankison HPR50 Refrigerated Dryer

SKU: HPR50

Price: ?0.00



Description

BETTER BY DESIGN

- Smooth bore, copper tube-on-tube heat exchangers deliver low pressure dew point performance
- Centrifugal separator efficiently captures liquid condensate at varying inlet loads
- Static condenser design – provides trouble free, quiet operation

RELIABLE CONDENSATE MANAGEMENT

- Electronic drain valve

EASE OF MONITORING

- Lighted on/off switch and dew point temperature indicator

OPTIONS

- Air bypass valve allows ease of service
- Wall mount bracket enables flexible installation

SAFETY FIRST — ENVIRONMENTAL FRIENDLY

- CFC free R134a refrigerant
- CSA approved

Specifications

SKU	Rated Flow (SCFM)	Rated Flow (m ³ /h)	Refrigerant	Voltage	Power (kW)	Inlet/Outlet Connections	Dimensions (H x W x D - in)	Weight (lb)
HPR50	50	85	R 134a	115V/E1/60	0.57	3/4 in NPT	22 x 20 x 20	101

Rated Flow Capacity – Conditions for rating dryers are in accordance with ISO 7183 (Option A2). Compressed air at dryer inlet: 100 psi (6.7 bar) and 100°F (38°C); ambient air temperature: 100°F (38°C); operating on 60 Hz power supply.

Operating Conditions

Maximum Inlet Air Pressure	Minimum Inlet Air Pressure	Maximum Inlet Air Temperature	Minimum Inlet Air Temperature	Maximum Ambient Air Temperature	Minimum Ambient Air Temperature
250 psi (17 bar)	30 psi (2 bar)	120°F (49°C)	40°F (4°C)	110°F (43°C)	45°F (7°C)

Hankison OEM/Distributor

Nuvair offers authentic parts and equipment manufactured by SPX Flow Hankison®. Beware of inexpensive aftermarket imitations labeled as "replacement," "OEM equivalent," "compatible," or "alternative," as they are not made by SPX Flow Hankison. Due to size, weight, specific requirements, or customer demand, some Hankison products may not be available for online purchase, and others may have extended lead times. To confirm compatibility with your existing equipment or to ensure the product meets your needs, please [contact the Nuvair Sales Team](#) for ordering assistance by email or phone.