

Drying Filter Cartridge for Lawrence-Factor HF

SKU: X96677

Price: ?147.17



Description

Specifications

Typical Application Drying Gas

Removes	H ₂ O, hydrocarbons, oil and particles
Micron Rating	2? particles
Dimensions	2.75" OD X 27" L
Contents	Molecular sieve

Filter Cartridge Warnings

DO NOT drop filter into housing.

REPLACE FILTERS AS A SET.

DO NOT use where operating temperature could exceed 120°F (49°C). Use of a temperature alarm is recommended.

HEAT & HUMIDITY shorten filter life.

DO NOT introduce large slugs of water into filter.

BLOW all lines and parts clear prior to installation.

DO NOT use where pressure surges are likely.

DO NOT use in system without earth ground.

REMOVE all protective seals and closures.

NOT FOR use in aircraft.

ALWAYS follow standard operating procedures (SOP) for producing breathing gases.

MAXIMUM USEFUL LIFESPAN is six months. Shelf life is two years.

Lawrence Factor® OEM/Distributor

Nuvair offers authentic parts and equipment manufactured by Lawrence Factor®. Beware of inexpensive aftermarket imitations labeled as "replacement," "OEM equivalent," "compatible," or "alternative," as they are not made by Lawrence Factor®, Inc. Some Lawrence Factor® products may have extended lead times. To confirm compatibility with your existing equipment or to ensure the product meets your needs, please [contact the Nuvair Sales Team](#) for ordering assistance by email or phone.