

30 Gallon, 200 psi Horizontal Volume Short Tank

SKU: 304946

Price: ?0.00



Description

PLEASE NOTE: The product is currently unavailable. Please see [SKU 302469](#) for a suitable alternative.

Specifications

This low-pressure air receiver is built in accordance with the ASME Section VIII Division I code latest addition. This model is 7 inches shorter in length than [SKU 302469](#) but offers the same volume. Vessels are "U" stamped and registered with National Board. Four tanks of different materials, finishes, and configurations are listed below. Quotes for special interior and exterior coating options available.

SKU	304946	304946-SS	304946-PC-BL01	KT-TANK-30H or KT-TANK-30H-SS
Volume	30 gal	30 gal	30 gal	30 gal
Cubic Feet	4	4	4	4
Material	Carbon Steel	304/304L Stainless Steel	Carbon Steel	Carbon Steel or 304/304L Stainless Steel
Exterior Finish	Standard Shop Primer	Aluminum Oxide Blast	Powder Coated Blue	Standard Shop Primer or Aluminum Oxide Blast
Interior Finish	As Welded, Unfinished	As Welded, Unfinished	As Welded, Unfinished	As Welded, Unfinished
Working Pressure (psi)	200	200	200	200
Operating Temperature	?400°F	-20°F to +200°F	?400°F	?400°F or -20°F to +200°F
O.D.	18 in	18 in	18 in	18 in
Length	31 in	31 in	31 in	31 in

Square Feet	13.2	13.2	13.2	13.2
Weight	97 lb	111 lb	99 lb	111 lb or 125 lb
Additional Equipment	Tank Only	Tank Only	Tank Only	<ul style="list-style-type: none"> • In-tank check valve, 30 CFM, 450 psi max • 200 psi ASME relief valve • 300 psi pressure gauge • Brass ball valve on outlet • Manual tank drain • Miscellaneous fittings and connectors