

MCH36 Fire Truck Compressor Package

SKU: 8049.2-FT

Price: ?0.00



Description

Features

- Motor start with soft starter
- Hour meter
- Pressure shutdown switch
- High temperature shutdown
- Low oil shutdown
- Interstage pressure gauges
- Electronic *Nuvair Pro CO* carbon monoxide monitoring with audible alarm and visible light indicator
- Electronic *Nuvair Pro H₂O* moisture monitoring with audible alarm and "change filter" indicator light
- Four (4) auxiliary shutdown connections for use with features such as door switches to ensure the compressor operates only with doors open for proper ventilation
- Filtration sold separately

Specifications

Model	8049.2-FT
Charging Rate*	27 SCFM (764 L/min)
CFM FAD	22.5 CFM FAD (637 L/min)
Motor	Three-phase
208-230 V / E3 / 60 Hz	48 A 20 hp (15 kW)
Pumping Unit RPM	1300

Max Operating Pressure 6000 psi (414 bar)

Number of Stages 4

Number of Fill Hoses 4

Condensate Drain Automatic

Sound Level @ 3 Meters 77 dB

Dimensions 48 x 40 x 32 in
(L x W x H) (122 x 102 x 81 cm)

Weight 750 lb (340 kg)

Lubrication Pressure lubrication, capacity 4 L

Air Quality Filtration package 6071-2X35-6K-FT sold separately

* Based on 80 cu ft cylinder from 500 to 3000 psi.