

MCH60 Enclosed & Silenced with Touchscreen Controller

SKU: 8059.2

Price: ?0.00



Description

System Components

- Two (2) Coltri MCH30 High Pressure Air Compressors
 - Each Compressor: 4 Cylinder, 4 Stage, Air Cooled
- Nuvair PLC & Touchscreen Controller
- Digital Multigas Analyzer: CO / Moisture / CO₂ / VOC
- Hour Meter
- Electric Motor: 208-230V, 440V, or 460V; 3 Phase, 50Hz or 60Hz
- Interstate Pressure Gauges
- (3) Condensate Separators on Each Compressor
- Large Stainless Steel Interstage Cooling Tubes
- Low Pressure Oil Pump with Filter
- Oil Level Sight Gauge and Oil Pressure Gauge
- Automatic Condensate Drains
- Loadless Start
- Low Oil Shutdown Switch
- Final Stage Head
- High Temp Switch set at 350°F
- (4) CAN-35 Filtration Towers
 - (3) Dryer Filter Elements
 - (1) Triplex Filter Element
 - 130,000 cu ft
- Aluminum Frame with Isolation Vibration Mounts

Specifications

Compressor Models	Two (2) Coltri MCH30
Charging Rate	20.4 SCFM (577 L/min) × 2
Filling an 80 cu ft tank from 500 psi	Total Charging Rate: 40.8 SCFM (1154 L/min)
Maximum Operating Pressure	6000 psi (414 bar)
Pumping Unit RPM	1100
Number of Stages	4 × 2
Dimensions (H×W×L)	71" (180cm) × 37.2" (94cm) × 67.8" (172cm)
Weight	~1425 lb (646 kg)
Lubrication	Pressure Lubrication, capacity 1.2 gal (4.5L) × 2
Air Quality	Grade E