

Breathing Air Filter Cartridge for LF-1003

SKU: X30249

Price: ?63.82



Description

An indicator strip is visible through the clear filter element. The indicator strip should be checked regularly for remaining filter life. It changes from blue to pink to white as the molecular sieve depreciates from moisture absorption.

Specifications

Typical Application Breathing Air (Grade D)

Removes	H ₂ O, CO, CO ₂ , hydrocarbons, oil, particles, taste & odor
Micron Rating	20? particles
Dimensions	1.75" OD X 7" L
Contents	Molecular sieve, activated carbon, CO catalyst

Breathing Air Filter Breakdown

Filter Element Warnings

DO NOT drop filter into housing.

REPLACE FILTERS AS A SET.

DO NOT use where operating temperature could exceed 120°F (49°C). Use of a temperature alarm is recommended.

HEAT & HUMIDITY shorten filter life.

DO NOT introduce large slugs of water into filter.

BLOW all lines and parts clear prior to installation.

DO NOT use where pressure surges are likely.

DO NOT use in system without earth ground.

REMOVE all protective seals and closures.

NOT FOR use in aircraft.

ALWAYS follow standard operating procedures (SOP) for producing breathing gases.

MAXIMUM USEFUL LIFESPAN is six months. Shelf life is two years.