

Quincy 5120 Kubota Diesel Base Mount Low Pressure Compressor

SKU: Q-5120-BM-K4F

Price: ?0.00



Description

Features

- Diesel Powered System
 - Kubota diesel Tier 4 Final D1105-E3B engine 25hp with electric start
- Loadless start with head unloaders
- Overpressure valve
- Drain valve
- Gate valve and plumbing
- Hayes PTO bearing block
- Engine instrument gauges and battery
- 13-gallon fuel tank with sight gauge and filter
- Additional remote fuel filter
- Two (2) ASME-rated volume tanks rated at 200 psi
- Four (4) diver manifold
- Heavy duty powder-coated stand-alone base mounted ("skid mount") frame
- Compressor and diesel engine equipped with independent vibration mounts
- Air quality test results

Options

- Optional WEG 25hp electric motor
- Breathing (CGA Grade D) air filtration and required accessories
 - Remote air intake to meet OSHA 29 CFR 1910.430(b) commercial diving operation requirements

- Carbon monoxide (CO) analyzer with high temperature shutdown
- IMCA Certification
- Certified frame package (required for offshore use) includes:
 - Certified designed frame with third-party engineer sign-off
 - Weld inspection
 - Pull test
 - Serial number plate
- Test/Tag/Certified gauges, hoses, and reliefs
- Nuvair 100 CFM air aftercooler
- 30-, 60-, or 120-gallon volume tanks

Specifications

Charging Rate	75 CFM (2123 L/min)
Engine / Motor	Diesel or Electric
Power	25 hp (18.5 kW) @ 3000 RPM
Max Operating Pressure	200 psi (14 bar)
Compressor RPM	1040
Number of Stages	2
Lubrication	Pressure
Air Quality	Industrial Air
Dimensions (L x W x H)	80 x 40 x 38.3 in (244 x 140 x 122 cm)
Weight	2650 lb (1202 kg)