

Custom 3/8" 250 psi Yellow Diving Hose & Hose Ends

SKU: K313AY-06-CUSTOM

Price: ?0.00



Description

K313AY-06 is a 3/8" lightweight, kink-resistance low pressure breathing air hose. Rated at 205 psi (17 bar), this hose has a clean, non-contaminating thermoplastic core tube and abrasion resistant cover. Meets MIL-H-2815 off-gassing requirements. Recommended hose ends: FS6X4 or MPT6X4-LF.

How to Order Your Custom Hose & Installed Hose Ends

1. Click the black CUSTOMIZE AND ADD TO CART button above.
2. Select the length of your K313AY-06 hose. Enter the length (in feet) in the "Qty" (quantity) window. For instance, if you need a 10-foot-long hose, enter "10" in the "Qty" box. Metric conversion: 1 foot = 30.48 cm.
3. Select the first hose end in the "Hose End #1" dropdown box. Only one hose end can be selected. You can also choose to have no hose end installed.
4. Select the second hose end in the "Hose End #2" dropdown box. Only one hose end can be selected. You can also choose to have no hose end installed.
5. Click "Add to Cart" Button. The total price will display in the Shopping Cart.
6. If the hose order needs to be edited, click "Edit" (pencil) icon in the Shopping Cart.
7. You can order multiple quantities of the same hose length and hose ends or revisit this page to order a new hose length/hose end combination.

Hose Specifications

K313AY-06 is a low-pressure hose that meets MIL-H-2815 off-gassing requirements. To order hose *without hose ends*, see [SKU K313AY-06](#) (3/8" 250 psi Yellow Diving Hose).

SKU	K313AY-06
Nominal	3/8"
I.D.	.375"
O.D.	.625"
Cover Material	Phthalate Free Yellow Flexible PVC Compound
Core Material	Phthalate Free Food Grade Clear Flexible PVC Compound
Working Pressure	250 psi @ 70°F
Minimum Burst Pressure	1000 psi @ 70°F

Compliance Notes for Air Breathing

When properly coupled with suitable fittings, this hose will satisfy the air supply line requirements for Type C respirators, as described in 30 CFR Part 11, Subpart J, 11.124-7, including the gasoline permeation test. This hose will also satisfy the “off-gassing tests”, as described in MIL-H-2815 F, Section 3.12.2 and 4.5.10.

Please note that NIOSH only certifies complete breathing respirators and does not issue certifications on individual components such as hoses. All replacement hoses for NIOSH-certified apparatus must have prior certification as part of that unit.

Hose End Choices

For a full listing of hose end choices, see RELATED PRODUCTS (below).

SKU NO-END

No Hose End Installed

SKU NO-END

Select this option if you do not want a hose end installed on Hose End #1 and/or Hose End #2. If chosen, the selected hose end/s will ship bare.

PLEASE NOTE: Custom cut hose and hose ends are special order items and are not returnable and are non-refundable. For additional information see our [RETURNS POLICY](#). For assistance with ordering custom hose and hose ends, or if your application requires "fractional foot" ordering (hose lengths that are not in one-foot increments, i.e. 14-foot, 7-inch hose length), please [contact the Nuvair sales team](#).