

NSS 2-Cylinder Fill Containment Station

SKU: NSS-2P

Price: ?0.00



Description

Standard Features

- All steel construction
- Grade 8 steel structural hardware
- Third party tested to meet or exceed NFPA 1901 standard
- Ergonomic design for easy operation
- Heads-up control panel allows monitoring and adjustments from a standing position
- Vertical blast tubes direct air blast and debris away from the operator should a failure occur
- Designed to fit all SCBA sizes
- 2216, 3000 or 4500 psi fill pressures
- Isolation valve for each fill pressure
- Safety relief valve for each fill pressure
- Supply shutoff valve
- Adjustable, self-venting regulator with inlet and outlet gauges
- Lined blast tubes reduce wear to SCBA cylinders
- Open door safety shutoff

Options

- Available fill devices:
 - DIN
 - International (yoke)
 - SCBA
- Auxiliary bulkhead fill connection

- Pneumatic door operation
- Integrated cascade cylinder controls
- SCUBA liners
- Ergonomic Heads-Up Customized Control Panel can include the following components:
 - Fill station supply line shutoff valve
 - Multiple storage bank control valve/s and gauge/s
 - Unregulated fill pressure gauge
 - High pressure regulator
 - Regulated fill pressure gauge
 - Fill pressure gauges and valves for individual cylinders
 - Three-way control valve for hot fill, storage bank/s, or cascade system
 - Nuvaire Pro O2 (oxygen) Analyzer for nitrox fills
 - Dump valve
 - Booster control
 - Door control switch
 - Control panel light
- Shop air outlet

Specifications

Model	Cylinders	Door Operator	Single/Dual Pressure	Cabinet Weight	Cabinet Size (L x W x H)
NSS-2P	2	Pneumatic	Single or Dual	560 lb (254 kg)	26 x 25 x 59 in (66 x 64 x 150 cm)

- Pneumatic door with interlock
- Fill panel shell without holes, gauges or valves
- Inlet pressure gauge and fitting only
- All other options must be added