

Mini Silent High Pressure Air Compressor

SKU: 8034 / 8034-13

Price: ?0.00



Description

Features

- Motor starter
- Automatic condensate drains
- Dial-a-pressure switch
- Automatic stop
- Hour meter
- Soundproof cabinet
- External oil sight gauge
- 5000 psi (345 bar) maximum pressure
- Grade E filtration
- Two (2) fill whips
- Stainless steel intercoolers

Options

- High temperature shutdown
- Low oil shutdown
- Interstage pressure gauges
- Visual CO/moisture indicator
- Additional filtration

Specifications

Model	MCH13	MCH16
Fill Time*	~11 minutes	~9 minutes
Charging Rate*	8.4 SCFM (238 L/min)	11.3 SCFM (320 L/min)
CFM FAD	7 CFM (200 L/min)	9.4 CFM (266 L/min)
Motor	Three-phase electric	Three-phase electric
208-230 V / E3 / 50 Hz	14 A SKU 8034.5-13	22 A SKU 8034.5
208-230 V / E3 / 60 Hz	14 A SKU 8034.2-13	22 A SKU 8034.2
380-415 V / E3 / 50 Hz	8 A SKU 8034.6-13	12.6 A SKU 8034.6
440-480 V / E3 / 60 Hz	8 A SKU 8034.3-13	10 A SKU 8034.3
Motor Power	5.5 hp (4 kW)	7.5 hp (5.5 kW)
Max. Op. Pressure	5000 psi (345 bar)	5000 psi (345 bar)
RPM	1370	1450
Number of Stages	3	3
Number of Fill Hoses	2	2
Condensate Drain	Automatic	Automatic
Fill Pressure Stop	Automatic	Automatic
Sound Level @ 3 m	72 dB	75 dB
Dimensions (L x W x H)	29.5 x 28.3 x 41.7 in (75 x 72 x 106 cm)	29.5 x 28.3 x 41.7 in (75 x 72 x 106 cm)
Weight	356 lb (161 kg)	356 lb (161 kg)
Lubrication	Splash lubrication, capacity (2) 1.8 L	
Air Quality	DIN 3188 - CGA Grade E - NFPA 1500 - EN12021	

*Fill time based on 80 cu ft cylinder from 500 to 3000 psi.