

Quincy 5120 Electric Mounted on 120 Gal Volume Tank

SKU: Q-5120-E-120T

Price: ?0.00



Description

Features

- Premium efficiency reliable electric motor
- Low oil carry over compressor rings
- LVD control
- Air cooler & ASME rated 120-gallon volume tank (gas receiver)
- Simple to operate, reliable and versatile

Options

- Low pressure regulator for downstream pressure
- CO and/or CO2 analyzers
- Audible and visual alarms for high temperature, low oil and carbon monoxide
- Shutdown for high temperature, low oil, low pressure, and carbon monoxide
- Air filtration to 0.003 ppm oil vapor
- 4 Diver manifold
- Motor Controller Star Delta or Soft Starter in 4X box
- Aftercooler
- 30 hp motor @ 95 CFM (2690 L/min)
- 200 gallon volume tank (gas receiver)
- California certified tank available
- TEFC 50/60Hz capable motor
- 250psi max

Specifications

Charging Rate	87 CFM (2464 L/min) @ 175 psi
Motor	230 / 415 / 460 V / E3 / 50 or 60 Hz
Motor Power	25 hp (18.6 kW)
Max Operating Pressure	200 psi (14 bar)
RPM	951
Number of Stages	2
Lubrication	Pressure
Air Quality	Grade D Breathing Air
Dimensions (L x W x H)	73 x 34 x 63 in (185 x 86 x 160 cm)
Weight	2060 lb (934 kg)