

Champion R30 Electric

SKU: LP-R30-10E.2-120T

Price: ?0.00



Description

Features

- Reliable electric motor
- High quality two-stage splash lubricated pump
- Centrifugal unloader - loadless starts
- Simple to operate, reliable and versatile

Options

- Custom frame with volume tank separate
- Honda gas or diesel engine
- Low pressure regulator for downstream pressure
- Air aftercooler
- CO and/or O2 analyzers
- Audible and visual high temperature alarm
- Low oil shutdown
- High temperature shutdown
- Breathing air filtration
- ASME rated 30-gallon or larger volume tank

Specifications

Model	LP-R30-7.5	LP-R30-10	LP-R30-15
Charging Rate	28.5 CFM (731 L/min)	34.8 CFM (985 L/min)	49 CFM (1388 L/min)

Model	LP-R30-7.5	LP-R30-10	LP-R30-15
Motor	7 hp (5.6 kW)	10 hp (7.5 kW)	15 hp (11 kW)
Maximum Operating Pressure	175 psi (12 bar)	175 psi (12 bar)	175 psi (12 bar)
208-230 V / E3 / 60 Hz	20A SKU LP-R30-7.5E.2	26A SKU LP-R30-10E.2	38A SKU LP-R30-15E.2
380-480 V / E3 / 50 Hz	11A SKU LP-R30-7.5E.6	15A SKU LP-R30-10E.6	21A SKU LP-R30-15E.5
440-480 V / E3 / 60 Hz	9A SKU LP-R30-7.5E.3	12A SKU LP-R30-10E.3	18A SKU LP-R30-15E.3
Dimensions (L x W x H)	73 x 24 x 56 in (185 x 61 x 142 cm)	73 x 24 x 56 in (185 x 61 x 142 cm)	73 x 24 x 56 in (185 x 61 x 142 cm)
Weight	820 lb (372 kg)	890 lb (404 kg)	890 lb (404 kg)
Lubrication	Splash	Splash	Splash