

Dwyer Gas Pressure Switch · Range 4–20" w.c. · Clearance!

SKU: 1996-20

Price: ?168.50



Description

NEW, UNUSED PRODUCT. DISCOUNTED PRICE. LIMITED QUANTITY.

Product Applications

- Gas furnaces
- Natural, manufactured or LP gas applications

Features

- Visible set point and on-off indicator simplifies operation and trouble shooting
- Compact size and low cost make it ideal for gas fired or gas equipment OEM applications

Specifications

Service:

Air, natural & manufactured gas, LP gas.

Wetted Materials:

Consult factory.

Temperature Limits:

32 to 110°F (0 to 43.3°C). -30 to 110°F (-34.4 to 43.3°C) for dry gas or dry air.

Pressure Limits:

45" w.c. (11.2 kPa) continuous; 10 psig (68.95 kPa) surge.

Switch Type:

SPDT.

Electrical Rating:

15 A @ 120 to 480 VAC, 60 Hz. Resistive 1/8 HP @ 125 VAC, 1/4 HP @ 250 VAC, 60 Hz.

Electrical Connections:

3 screw type, common, normally open, normally closed.

Process Connections:

1/8" female NPT or 1/4" male NPT.

Vent Connection:

1/8" female NPT.

Mounting Orientation:

Diaphragm in horizontal position. Consult factory for other position orientations.

Set Point Adjustment:

Screw type with visible indicator, inside conduit enclosure.

Weight:

1 lb 2.3 oz (349 g).

Compliance:

CE, CSA, FM, UL.