

Non-Vented Reducing Regulator 6000 psi In > 0–5000 psi Out Aluminum · Low Temperature

SKU: 415-5000-NV-L

Price: ?358.00



Description

Typical Applications

- Component testing
- Air tank fill stations
- Firefighting air systems
- Instrumentation and calibration panels
- Process industry control
- Shipboard and offshore air and gas control
- Aircraft service equipment
- Electronic industry rare gas flow
- Vehicle CNG stations

Specifications

Type	Reducing Regulator
Special Features	Non-Vented Low Temperature
PSI Out	0 to 5000 psi
Hand Loaded/Operated or Dome/Air Operated	Hand/Spring Loaded
Maximum Rated Pressure	6000 psi
Outlet Pressure Range	50–5000 psi
Outlet Pressure Rating	6000 psi

Inlet Port Size	2 ea 1/4" FNPT (One Gauge, One Inlet)
Outlet Port Size	2 ea 1/4" FNPT (One Gauge, One Outlet)
Flow Coefficient (Cv)	0.06 (equals 0.07 in orifice)
Outlet Pressure Variations with Inlet Pressure Variations	70 psi rise/1000 psi inlet drop
Leakage	Bubble tight
Weight	1.6 lb (710 g)
Overall Length	5.5"
Round Diameter	2.25"
Minimum Temperature	-60°F (-51°C)
Body Materials	Anodized Aluminum
Internal Materials	Anodized Aluminum, Brass, Stainless
Seal Materials	Kel-F, Nitrile
Special Note	Not oxygen cleaned
Accessories	Mount Ring (SKU 657)
Repair/Service Kit	839-5000-NV-L