

# Dive Shop Air/Nitrox Turnkey Package #2

SKU: PKND2-315

Price: ?49,724.00



## Description

PLEASE NOTE: Dive shop packages are not available for purchase online. Each package is custom-built to customer specifications. This page reflects the current base price for Dive Shop Air/Nitrox Turnkey Package, SKU PKND2-315-E.6 · 380-415V/E3/50Hz. Your final purchase price may differ. Please [contact](#) the Nuvair Sales Team to place your order.

## Package #2 Includes

- Nuvair Voyager 315 Nitrox System
- Six (6) 4500 psi Storage Tanks with Connecting Hardware for a total of 2922 cu ft of air storage
- Two Bank Fill Panel (SKU PN-2BA)
- High Pressure Hoses & Fittings · 3 x 12' (SKU 520N-4)

## Voyager 315 Features

- Fully Featured for Automatic Operation
- Enclosed and Silenced Cabinet
- Modular, Two-Part Cabinet System Fits Through Most Doors
- Nuvair Membrane System Delivers EAN<sub>x</sub>40 at 10 CFM
- Champion EK76 Rotary Screw LP Compressor
  - Pump Rated at 29 ACFM @ 175 psi for Membrane Supply
  - High Quality 10 hp Electric Motor
- Three-Stage High Pressure Compressor
  - Pumps Air to 4500 psi (310 bar); Nitrox to 3800 psi (262 bar)
  - Pump Rated at 10.6 CFM powered by a 7.5 hp Electric Motor
- Hankison 3-Stage LP Air Filtration
- Refrigerated Air Dryer
- Automatic Dial-a-Pressure Shutdown

- Automatic LP/HP Condensate Drains
- Cabinet Temperature Gauge
- Push Button On/Off Motor Starters
- LP and HP Compressor Hour Meters
- External Oil Sight Gauge, Fill and Drain
- Cooling Fans
- High Cabinet Temperature Shutdown
- Two (2) Pro O<sub>2</sub> analyzers (one permeate and one fill oxygen analyzer)
- One (1) CAN-35 Filtration Tower processes 26,000 ft<sup>3</sup> of Grade E air

## **Voyager 315 Advantages**

- Complete state-of-the-art LP/HP nitrox generating system
- Simplest, most cost-effective solution available
- None of the costs, hassles, or hazards of oxygen blending
- Semi-silenced enclosure reduces operating noise

## **Package #2 Options**

- CO<sub>2</sub> Scrubber (SKU 6070.5, as pictured)
- 6000 psi Storage Tanks (SKU NUVT6000-W) for 3900 cu ft of air storage
- Standalone Volume Tank in lieu of Refrigerated Air Dryer
- Second CAN-35 Filtration Tower (as pictured)
- Pro H<sub>2</sub>O (moisture), Pro CO (carbon monoxide), and/or Pro CO<sub>2</sub> (carbon dioxide) analyzers (As pictured, Pro CO · Pro CO<sub>2</sub> installed)
- Upgraded Fill Panel
- Available Power Supplies: 208-230V/E1-E3/50-60Hz, 380-415V/E1-3/50 Hz, or 440-480V/E3/60Hz