

# Nomad LP Gas-Powered Breathing Air Compressor • Loaded

**SKU:** LP-B15-G-L

**Price:** ?0.00



## Description

Weighing in at under 240 pounds, this is a portable compressor with great air delivery. Diver air filtration is not included with this compressor but is available as an option to produce CGA Grade D breathing air.

## Features

- Two Stage, Two Cylinder Breathing Air Compressor
- Pneumatic Load Control for Gas Engine
- 3-Stage Grade D Breathing Air Filtration Pack<sup>1</sup> (**SKU 6063.1**)
- Pro CO Carbon Monoxide (CO) Monitor<sup>1</sup> (**SKU 9625-B**)
- Quick-Disconnect Remote Air Intake<sup>2</sup> (**SKU NUVRAI-BX**, as pictured)
- Air-Cooled Aftercooler (**SKU ACAC-25**)
- Digital Hour Meter
- FDA Food Grade synthetic Nuvair 455 oil
- Pressure activated throttle
- Oil sight gauge
- Integrated twin volume tanks with drains rated to 160 psi
- 4" Pressure Gauge
- All Terrain Tires

## Recommended Options

- Air Test Kit (**SKU 1XTEST**)
- Dive Hose and Hose Ends (**SKU K313AY-06-CUSTOM**)

## Specifications

<b>Model</b>		<b>LP-B15-G</b>
<b>Cylinders/Stages</b>	2/2	
<b>Displacement / CFM</b>	13 CFM (368 L/min) @ 1100 RPM	
<b>Engine</b>	4.8 hp (3.6 kW) Honda GX160	
<b>Max Operating Pressure</b>	145 psi (10 bar)	
<b>Air Tank Volume</b>	(2) 2.9 gal (11 L)	
<b>Dimensions (L x W x H)</b>	35 x 27 x 32.5" without handles (89 x 69 x 83 cm)	
<b>Weight</b>	175 lb (79 kg)	

## Notes

<sup>1</sup> OSHA Standards for Respiratory Protection · [1910.134\(i\)\(7\) CFR](#): "For oil-lubricated compressors, the employer shall use a high-temperature or carbon monoxide alarm, or both, to monitor carbon monoxide levels. If only high-temperature alarms are used, the air supply shall be monitored at intervals sufficient to prevent carbon monoxide in the breathing air from exceeding 10 ppm." [?10 pm carbon monoxide meets CGA Grade D breathing air requirements.]

<sup>2</sup> Remote air intake required to meet OSHA standards for breathing air.