

# Pro CO Alarm Analyzer w/ Relay in Waterproof Box

**SKU:** 9626.5

**Price:** ?961.00



## Description

## Specifications

<b>Flow Rate</b>	0.5-1 L/min
<b>Resolution</b>	1 ppm
<b>Repeatability</b>	<+5%
<b>Accuracy</b>	±5%
<b>Sensor Type</b>	Electrochemical
<b>Expected Sensor Life</b>	>24 months in normal use from date of manufacture
<b>Range</b>	0-50 ppm CO
<b>Alarms</b>	Two user-programmable audible and visual alarms
<b>Response Time</b>	<50 seconds over complete temperature range
<b>SPDT Relay Ampacity</b>	10A @ 230VAC/30VDC
<b>Operating Temperature</b>	14° to 122°F (-10° to 50°C) continuous -4° to 122°F (-20° to 50°C) intermittent
<b>Operating Humidity</b>	Non-condensing: 15-90% continuous; 0-99% intermittent
<b>Storage Temperature</b>	14° to 140°F (-10° to 60°C)
<b>Power</b>	110/220V Wall Plug-in (International) Power or 1150mAh Rechargeable Lithium Battery with charger 12V/24V Input
<b>Dimensions (L x W x H)</b>	3.9 x 8.7 x 7.5 in (9.9 x 22.1 x 19.1 cm)

<b>Weight</b>	2 lb 8 oz (1.27 kg)
<b>Warranty</b>	12 months
<b>Replacement Sensor</b>	<a href="#">SKU 9501</a>

PLEASE NOTE: Never expose gas sensors to pressure or you may cause damage and/or false readings. Damaged sensors will not provide accurate gas analysis. Inaccurate gas analysis can lead to serious personal injury or death. Most gas analyzers can be used to analyze a regulated gas sample flow, the contents of a gas cylinder, or the flow from a regulator. The flow rate of gas must equal 1-5 L/min. To produce this flow, a [Flow Restrictor and Regulator](#) may be required.